

C2004 Small Dual Centrifuge

C2004. (230V 50/60Hz). 1.C2004. (110V 60Hz)



Display indicative only

Speed max	500-4,000 Rpm (10 Rpm steps)
Rcf max	2,200 G
Timer	0-99 Mins & Hold (30 sec steps)
Dims HWD	275 x 325 x 470mm
Weight	21.8Kg (without rotor)
Power	160 watts
Memory	10 programs
Accel Rates	10 programs
Decel Rates	10 programs

Swing Out Rotor

Adaptors required see page 17

Rotors 4000 Rpm



(Requires 4 buckets B5010)

Rotor	BRK5324	BRK5308	BRK1000
Rotor type	24 x 15ml	8 x 50ml	4 x 100ml
Tube size max	17 x 120mm	30 x 120mm	45 x 100mm
Minimum speed Rpm	500	500	500
Maximum speed Rpm	4,000	4,000	4,000
Maximum rcf (G)	2,200	2,200	2,200
Radius max cms	12.3	12.3	12.3
Sample tube angle °	30	30	0
Acceleration time (secs)	35	35	25
Deceleration time (secs)	35	35	25
Autoclavable (frequency)	121°C (20)	121°C (20)	121°C (20)

Reducers (Pack of 4)



BRK5324



BRK5308



Rotor	BRK5324	BRK5308
Part number	RM05 (5ml)	RM15 (15ml)
Tube size max	13 x 80mm	17 x 120mm
Part number	RM10 (10ml)	RM25 (25ml)
Tube size max	13 x 100mm	25 x 100mm